


THE INTERNAL THRESHOLD SHOULD BE SMOOTH & LEVEL. IT IS ADVISED THAT THE EXTERNAL THRESHOLD SHOULD BE AWAY FROM THE OPENING TO HELP PREVENT WATER INGRESS.

CLIENT / SITE :	
OPERATION :	ELEC / CHAIN / PUSH UP
HAND OF OPERATION :	VIEWED FROM INSIDE (V.F.I) LH / RH
POWER SUPPLY (if elec.) :	1PH / 3PH
PANEL FINISH :	POLYESTER / PLASTICOL
EXTERNAL COLOUR & REFERENCE :	
INTERNAL (RAL 9010 WHITE STD)	
WICKET DOOR REQ'D (positioned centrally)	YES / NO
WICKET DOOR HINGE (V.F.I)	LH / RH
VISOR PANELS	OR NO ROWS
IN + PANEL(S) FROM BOTTOM	OR WINDOWS
OTHER:-	



DESCRIPTION: INSTALLATION CLEARANCES - VERTICAL LIFT TRACKS c/w CONSOLES - 40mm THICK PANEL

indupart

DATE :	DWG NO.:	REV:
CHANG. BY :	INSTALL 9	A
DATE :	SHEET:	@indupart 2008

All dimensions in mm, unless specified. Tolerance + or - 5mm. All dimensions are based on Kinglign standard 40mm thick panels & standard 51mm (2") track.