indupart.co.uk

Foodsafe High Speed Door



0161 432 6655 | sales@indupart.co.uk | www.indupart.co.uk

Northern Sales, Distribution Centre & Production Warehouse The Door Centre, Discovery Park, Crossley Road, Stockport, SK4 5BW







Raising Standards Safety Assured

Performance

Maximum Dimensions: 4000mm x 3800mm Frame: Guides and side brackets in PE, non-supporting Covers: Motor covers in stainless steel 304, included as standard Power Supply: 230 VAC, mono-phase Control cabinet: Plastic, with IP65 protection degree Safety: Barrel type inferred photocells Installation: Easy installation due to factory semi-assembled frames and components Temperature: Wide range operating temperature +2°C to +40°C Humidity: Up to 80% condensation free)

Features

Hygiene and speed - two in one solution Non rusting frame and food friendly High level of sound and temperature insulation Phase invertor for precision and speed Pre-wired controls and cabling Opening speed up to 2.5 m/s

Optional Extras

Fully Automatic Operation: High-speed door may automatically open when a radar or proximity sensor is triggered.

Automatic interlock: Both doors may be interlocked together, thus while one is working, the other is blocked for operation preventing double closing.

Wireless control without batteries: To minimise the number of run cables, a door may be equipped with wireless push buttons with unique "battery free" technology.

Curtain

Type: Completely flexible curtain, with self-relocating system. Material: PVC as standard supply. Optionally in FDA approved PU. Insulation: High-level acoustics and thermal insulation. Colours: More than 15 colours available.

Standard Colours



White



RAL 7038 Dusty Grey

RAL 7037







Oyster White











RAL 9006 Silver



Black

Insulated Colours



RAL 7035 C Light Grey



RAL 6026 C Opal Green



Food and Drug Administration (FDA) Colour



Curtain Repairs

We can repair all major brands of High Speed Doors. Patch repair and full curtain replacements are available at competitive prices at our off site facility. Please note: For all curtain repairs a drawing will need to be supplied for us to get a close replica of the existing curtain.

RAL 2004 Pure Orange