



Roller Shutter

(Product Range)

   /indupart  /company/indupart-ltd

0161 432 6655 | sales@indupart.co.uk | www.indupart.co.uk

Northern Sales, Distribution Centre & Production Warehouse
The Door Centre, Discovery Park, Crossley Road, Stockport, SK4 5BW



Raising Standards
Safety Assured

Applications

Industrial

Industrial roller shutters are typically utilised on large apertures up to 72m². Factories can be susceptible to sustained attack due to their isolated locations and our high security shutters offer increased protection. Foam filled profiles provide heat and sound insulation and high speed variants assist with frequent traffic and heavy duty use.

Options Include

Tubular or outboard motor power, depending on size and application, with high speed options available.

A range of colours and finishes available, including powder coating.

Optional insulation, or vision profiles to facilitate light ingress and air flow.

Suitable For

Factories
Warehouses and distribution
Cold storage centres
Agricultural buildings
Loading bays

Commercial

Commercial properties have a diverse set of security requirements. Protect products from theft, prevent vandalism to windows or add shading and climate control, all while maintaining business aesthetics. Suitable for all opening sizes, with various security levels available.

Options Include

A choice of colours, including powder coating to match brand colours.

Solid, insulated and vision profiles to suit all commercial requirements.

Variety of control options including keypads, remote control and grouped operation for multiple shutters.

Suitable For

Offices
Banks
Restaurants and bars
Schools and hospitals
Council and Government

Applications

Retail



Out-of-hours shops are a prime target for opportunistic and career criminals. A retail security shutter provides a deterrent and prevents these types of attacks. See-through designs prevent displays from being hidden away and are sensitive to existing frontage.

Options Include

Vision profiles display products while closed, including the transparent polycarbonate Eurolook shutter.
Powder coating to match existing colour schemes.
Secure control options, including keypads and remote control operation.

Suitable For

Shops
Supermarkets
Retail Parks
Shopping Centres
Markets

Domestic



Add insulation, shading and security to windows and doors with a low maintenance residential security shutter. Discrete housings and powder coated finishes provide quality aesthetics, while optional ventilated profiles allow air flow and partial vision, even while the shutters are lowered.

Options Include

Compact slat and roll sizes for small to medium openings.
Wide range of styling options, including colour matching and circular housings.
Motorised operation with convenient control via wall switches, remote controls or integration into home automation systems.

Suitable For

Houses
Apartments
Holiday homes
Nursing and care homes
Student accommodation

Aluminium Security Shutters

Aluminium security shutters offer numerous benefits, including compact housings, high security and quiet, smooth operation. Aluminium is suitable for commercial, retail and domestic shutters. It is strong, durable and customisable to match the requirements of any job.

Profiles can be solid, solid and insulated, perforated, punched or arranged as a grille to maximise light flow and visibility. Various security levels are available.



M411 / T55 / M511

Insulated | Medium Security

Versatile insulated shutter for small to medium openings.

- Compact, tightly-rolling 43mm or 55mm profile.
- Box sizes as small as 150mm.
- Foam insulation for improved U-values.
- Optional light and ventilation slots.
- Wide range of standard colours available.
- Electric or manual operation.

M411



T55



M511



E37 / V37 / P37

Extruded | Vision | High Security

High security extruded shutter for small to medium openings.

- Smallest profile, at 37mm.
- Box sizes as small as 150mm.
- Extruded aluminium construction for optimum strength.
- Solid and vision (punched and perforated) profiles, which can be combined if required.
- Powder coating available on request.
- Electric or manual operation.

E37



V37



P37





T77 / E77 / V77 / P77

Insulated | Vision
Extruded | High Security

Insulated or extruded shutter for a diverse range of applications.

- Foam-filled or extruded 77mm profile.
- Solid and vision (punched and perforated) profiles, which can be combined if required.
- Wide range of standard colours available.
- Powder coating available on request.
- Electric or manual operation.

T77



E77



V77



P77



Tube & Link

Vision | Medium Security

Grille-like shutter with openings for maximum vision and air flow.

- Lattice shutter made from tube and link components.
- Brick formation as standard, which can be customised.
- Steel or aluminium box and guide system.
- Tubes enclose steel rods for strength and security.
- Powder coating available on request.
- Electric operation with tubular or outboard motor.



Eurolook

Vision | High Security

Transparent barrier designed for high security levels.

- Solid transparent polycarbonate links allowing vision and light flow.
- Suitable for medium to very large openings.
- Externally tested for high security (Class 3, according to SKB's ENV 1627-1630 standard).
- Frosted and ventilated variants available.
- Electric operation with tubular or outboard motor.



Steel Security Shutters

Steel products are heavyweight by nature and are traditionally popular in commercial, retail and industrial applications. They are available in solid, perforated, punched and insulated variants and can be powder coated any RAL / BS colour, with a range of control options.

All security levels are available, and our FS fire shutters have been tested and approved for resistance from 1 to 4 hours.




S76 / V76 / P76

Vision | High Security

Extruded single skinned shutter with optional vision profiles.

- 76mm single skinned slat for exceptional strength.
- Steel or aluminium box and guide system.
- Solid and vision (punched and perforated) profiles, which can be combined if required.
- Powder coating available on request.
- Electric operation with tubular or outboard motor or manual spring and lock.

S76



V76



P76



i95

Insulated | Medium Security

Insulated shutter with exceptional U-values.

- Foam-filled 95mm profile offering U-values of 1.1 W/m2 K.
- Maximum area of 35m2.
- Powder coating and Plastisol laminated finishes available on request.
- Electric operation with tubular or outboard motor.
- High speed motor option available for rapid rise applications.





i100

Insulated | High Security

Insulated shutter with large 100mm profile.

- Foam-filled 100mm slat with 81mm profile.
- Powder coating and Plastisol laminated finishes available on request.
- Capable of covering very large areas up to 72m2.
- Electric operation with tubular or outboard motor.



FS Fire Shutters

Fire Rated | Extruded | High Security

Fire rated for 1, 2 or 4 hours, with alarm system integration.

- Solid steel shutter with fire rating.
- Externally tested by Exova Warringtonfire for 1, 2 or 4 hours (under BS EN 1634-1:2008 and assessed to BS EN 476-22:1987).
- Fire alarm integration for automatic operation in the event of a fire.
- Barrel frames provide support for larger shutters.
- Electric operation with tubular or outboard motor.



Aluminium

	Application				Security Level		Slat Feature					Max Size*	
	Commercial	Retail	Industrial	Domestic	Medium	High	Insulated	Extruded	Vision	Fire Rated	Powder Coating	Width (m)	Area (m²)
M411	●			●	●		●					3.4	8
T55	●			●	●		●					3.5	10
M511	●			●	●		●					5	12
E37	●			●	●			●			○	4	12
V37	●			●	●			●	●		○	4	12
P37	●			●	●			●	●		○	4	12
T77	●	●			●		●				○	5.5	16
E77	●	●			●			●			○	6.5	25
V77	●	●			●			●	●		○	6.5	25
P77	●	●			●			●	●		○	6.5	25
Eurolook	●	●			●			●	●			12	72
Tube & Link	●	●			●				●		○	12	72

Steel

	Application				Security Level		Slat Feature					Max Size*	
	Commercial	Retail	Industrial	Domestic	Medium	High	Insulated	Extruded	Vision	Fire Rated	Powder Coating	Width (m)	Area (m²)
S76	●	●	●		●			●			○	12	72
V76	●	●	●		●			●	●		○	12	49
P76	●	●	●		●			●	●		○	12	49
i77	●		●		●		●				○	8	42
i95	●		●		●		●					8	35
il00	●		●				●				○	12	72
FS 60/120/240	●		●		●			●	●	●		12	50

*Calculated based on overall size for aluminium products (including box and guides), and opening size for steel products.
Maximum sizes are achieved with an outboard motor setup where available. Tubular motors and manual operation available for smaller shutters.

●

 Standard

○

 Optional