



Belt High Speed Door (Fold Up)

    /indupart  /company/indupart-ltd

0161 432 6655 | sales@indupart.co.uk | www.indupart.co.uk

Northern Sales, Distribution Centre & Production Warehouse
The Door Centre, Discovery Park, Crossley Road, Stockport, SK4 5BW



Available with
GfA operators



Raising Standards
Safety Assured

Design

The rapid fold-up Belt door is the ideal solution for medium/large sized bays, especially where high wind resistance is a must.

Options

Safety Light Grid: Ensures maximum safety for through traffic, and personnel, avoiding completely direct contact with the curtain.
Insulated Fabric: When using an insulated fabric, temperature insulation and sound proof characteristics will improve considerably.

Sloping thresholds: The bottom of the curtain can be easily adjusted to compensate for some slopes at the door threshold.

Features

Wide range of applications: Hangers, garages, waste management sites, loading docks, internal room separation, high-traffic production areas, etc.

Opening speed: up to 1,0 m/s

Withstands high wind loads, Heavy duty gear motor drive unit, Fully automatic or dead man operation.

Technical Data

Application: Inside / Outside

Maximum dimensions*: 20,000mm W x 15,000mm H clear opening width & height

Opening / closing operating speed: Up to 1,0 m/s

Range temperature: -30°C to + 70°C

Wind Resistance EN 12424:

Up to 8000mm W x 8000mm H

Up to 5000mm W x 5000mm H

Up to 3000mm W x 3000mm H

Class 2

Class 3

Class 4

Frame EN 12604:

Galvanised steel

Stainless steel AISI 304-316

Powder coated

Standard

Optional

Optional

Roller:

Galvanised steel

Stainless steel AISI 304

Standard

Optional

Control cabinet:

IP55 metallic, powder coated

IP55 stainless steel, AISI 304-316

PVC IP66

Standard

Optional

Optional

Motor position:

Frontal LH/RH

Lateral LH/RH

Pendular

Standard

Standard

Optional

Fabric door curtain:

Polyvinyl chloride (PVC)

PVC insulated

Standard 900 g/m² thickness 0,9mm

Optional 1300 g/m² thickness 3mm

Standard Colours



RAL 9016
Traffic White



RAL 1013
Beige



RAL 5015
Light Blue



RAL 5010
Dark Blue



RAL 1003
Yellow



RAL 2004
Orange



RAL 7035
Light grey



RAL 7038
Medium Grey



RAL 7037
Dark Grey



RAL 6026
Green



RAL 3002
Red



RAL 9006
Silver



RAL 9005
Black

Curtain Repairs

We can repair all major brands of High Speed Doors. Patch repair and full curtain replacements are available at competitive prices at our off site facility. **Please note:** For all curtain repairs a drawing will need to be supplied for us to get a close replica of the existing curtain.

0161 432 6655 | sales@indupart.co.uk | www.indupart.co.uk

Windows: Two rows 850mm x 300mm or 1100mm x 300mm (WxH)

Windows type:

Transparent / mesh
Mesh with covers

Standard - commonly used for ventilation
Optional - useful in cold periods of the year

Control system:

Logic board with contactors
Logic board inverter based

Standard/tri-phase 230V/400V
Optional/single phase 230V

Positioning system:

Mechanical limit switches
Digital encoder***

Standard
Optional

Drive unit EN 12604: 3-phase motor with active brake, IP54

Safety devices EN 12453:

Infrared photocells
Wireless bottom edge
Light barrier
Microwave radar

Standard
Standard
Optional
Optional

Emergency opening:

Manual crank handle
Counter-balance

Standard
Optional


with automatic or on demand opening***
Optional**

UPS

* Other sizes of the door may be available on request

** Limitations apply, check with our sales team

*** Only with inverter



Available with
GfA operators