



Flexirun Cold High Speed Door

(Self Repairing Roll Up with
High Thermal Excursion)

    /indupart  /company/indupart-ltd

0161 432 6655 | sales@indupart.co.uk | www.indupart.co.uk

Northern Sales, Distribution Centre & Production Warehouse
The Door Centre, Discovery Park, Crossley Road, Stockport, SK4 5BW



Available with
GfA operators



Raising Standards
Safety Assured

Design

FlexiRun COLD is ideal between rooms with different ambient temperatures, be they negative, or positive.
Both the motor windings, and the guides contain heater traces.

Options

Complete Anti-Rust Solution: Door frame along with motor cover and control cabinet, may be supplied in stainless steel AISI 304 or 316.
Optional digitally printed logos and/or warnings can be printed on the door curtain.

Features

Opening speed: up to 1,5 m/s
Designed for cold storage applications, Double-wall insulation system, High efficiency and energy saving, Phase inverter for precision and speed, Pre-wired controls and heating system. Low frost-up factor on curtain surfaces.

Technical Data

Application: Inside / Outside
Maximum dimensions*: 3500mm W x 5500mm H clear opening width & height
Opening / closing operating speed: Up to 1,5 m/s 0,8 m/s, adjustable
Range temperature: -35°C to + 70°C with optional required accessories
Wind resistance EN 12424: Class 2 standard

Frame EN 12604:
Galvanised steel **Standard**
Stainless steel AISI 304-316 **Optional**
Powder coated **Optional**



Roller:
Galvanised steel **Standard**
Stainless steel AISI 304 **Optional including support bearings in composite material**

Control cabinet:
Metallic, powder coated control cabinet with IP55 protection degree **Standard**
Stainless steel, AISI 304-31 **Optional**
PVC-IP66 **Optional**

Motor position: Lateral LH/RH

Door leaf:
Double curtain polyvinyl chloride (PVC) with air cushion **Standard 900 g/m² thickness 0,9mm**
FDA **Optional**
Anti-static **Optional**

Standard Colours



Curtain Repairs

We can repair all major brands of High Speed Doors. Patch repair and full curtain replacements are available at competitive prices at our off site facility. **Please note:** For all curtain repairs a drawing will need to be supplied for us to get a close replica of the existing curtain.



Available with GFA operators

Windows:
No windows **Standard**
850mm x 300mm WxH **Optional**

Control system: 230V AC logic board, inverter based

Positioning system:
Mechanical limit switches **Standard**
Digital encoder **Optional**

Drive unit EN 12604: 3-phase motor with active brake, IP54

Heating system:
Hot air blower **Optional**
Timer **Optional**
Heating cable for frame & motor **Optional**
Heating cable for electric box **Optional**

Safety devices EN 12453:
Photo electric photocells **Standard**
Curtain anti-jamming sensor **Standard**
Light barrier **Optional**
Microwave radar/wireless safety edge **Optional**

Emergency opening:
Manual crank handle **Standard**
Counter-balance **Optional**

with automatic or on demand opening***

UPS **Optional limitations apply**

* Other sizes of the door may be available on request

